



The 3-Axis CNC controlled panel processing machine LEPUS - II L is intended for cutting, v-channel opening and similar operations on various composite panels and plates.

Thanks to its unique automatic tool replacement system, the machine reduces set replacement time to 2.5 seconds and minimizes the time loss with tool replacement process. In addition, the machine enables processing of wooden, plastic and various materials by replacement of the milling cutter.

LEPUS - II L

CNC ACP Processing Machine (3 Axis, 4 Spindles) - 7 m

MACHINING LENGTHS	
X Axis (Longitudinal)	1600 mm
Y Axis (Lateral)	7000 mm
Z Axis (Vertical) – without tool	200 mm
POSITIONING SPEED	
X Axis (Longitudinal)	55 m/min
Y Axis (Lateral)	55 m/min
Z Axis (Vertical)	15 m/min
B Axis (Rotational Movement)	10°/sec.
TOTAL POWER CONSUMPTION	25,5 kW
SPINDLE	
Power	7.5
Maximum rotation speed	18000 rpm
Tool Holder	ıso 30
Cooling Type	Elektro Fan
POWDER SUCTION	
Power	3 kW
Engine rpm	3000 rpm
VACUUM PUMP	
Power	2 x 7.5 kW
Engine rpm	3000 rpm
CONTROL UNIT	
Data transfer over remote network connection, CF Card and USB	•
CNC control unit	•
Remote Connec⊠on	•
OPERATIONAL AREA	
Dust extractor	•
Vacuuming independent sections	•
Number of vacuum tables	8
Automatic tool length measurement	•
Pneumatic reference stop for panel positioning along X axis	2
Pneumatic reference stops for panel positioning along Y axis	9
Lighted barrier system that blocks access to the working area	0
Metal fence protecting three sides	•

• Standard o Optional

Özçelik Makina continuously improves its products and offers new and modern solutions for PVC and Aluminum Profile Processing. Accordingly, Özçelik reserves the right to change the information in this document without notice. All dimensions and weights are reference values. Valid from January 2023